



storing address & register & (initialization OR startup)

Search

OSAPA Pilot: Search Engine I (long site list) Web Search

Results 1 - 10 for storing address & register & (initialization OR startup). (0.20 seconds)

Refine results for storing address & register & (initialization OR startup):

Distros: debian, redhat, suse and ubuntu.	kernel.org: Linux kernel code repository.	Me
Linux Man Pages	Silicon Graphics Documentation	Lir
BSD operating systems	freshmeat: catalog of UNIX applications.	Or
Desktop Projects: GNOME, KDE, X, freedesktop.	SourceForge: host website for OSS development projects.	Er

hw-disk-ide

initialization. All parameters must be set for the selected simulated drive (N=0 ... The "data port" register lives at address 0 in the command-block-bus. ...
sources.redhat.com/eid/component-docs/hw-disk-ide.html - 13k - [Cached](#)

Kernel initialization

First what is done is the register EFLAGS is set to a predefined value of ... out what CPU it is running on, storing the value found in a variable _cpu ...
www.freebsd.org/doc/en/books/arch-handbook/boot-kernel.html - 24k - [Cached](#)

Bus Address Spaces (Writing Device Drivers) - Sun Microsystems

Configuration space is used primarily during device initialization. It determines the location and size of register sets and memory buffers located on the ...
docs.sun.com/app/docs/doc/802-5900/6i9kj7oop?a=view - 28k - [Cached](#)

Mozilla/Netscape Address Book "HotSync"

Since Mork is in-memory database, reading the data and storing it in memory ... wrapper around it so that module registration is automatic during startup. ...
www.mozilla.org/mailnews/arch/MozAB_Palm_HotSync.html - 48k - [Cached](#)

JCS - Remote Auxiliary Cache Client / Server

Registry used to register and provide the # IRemoteCacheService service. ... If we startup another remote server listening to port 1103, (ServerB) then we ...
jakarta.apache.org/jcs/RemoteAuxCache.html - 17k - [Cached](#)

Summary of changes from v2.6.4 to v2.6.5 ...

fixed the wrong register initialization on ALC655/658. new USB device on port 2, assigned address 8 > Initializing USB Mass Storage driver. ...
www.kernel.org/pub/linux/kernel/v2.6/ChangeLog-2.6.5 - 358k - [Cached](#)

Using the GNU Compiler Collection (GCC)

Because always storing floating-point arguments on the stack is inefficient and rarely needed, Do not use register r13 to address small data however. ...
visual-mingw.sourceforge.net/doc/gcc-3.2.3/RS-6000-and-PowerPC-Options.html - 25k - [Cached](#)

2. Installation and Startup Problems (Solstice Enterprise Manager ...)

During MIS initialization, the following kinds of errors occur: Storing ping_up condition failed! Adding ping_up condition failed! ...
docs.sun.com/app/docs/doc/802-5967/6i9mj4eed?a=view - 25k - [Cached](#)

Compiling Java for Embedded Systems

This is safe, because the Java verifier does not allow storing an integer ... This means the actual initialization needed at run is very little most of it ...
www.redhat.com/support/wpapers/cygnus/cygnus_compiling/compiling.html - 16k - [Cached](#)

Troubleshooting Installation and Startup Problems

Storing ping_up condition failed! Adding ping_up condition failed! Possible Cause: These error messages occurred during MIS initialization. ...

docs.sun.com/source/816-2001/TBI_startprobs.html - 39k - [Cached](#)

[1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#) [Next](#)

storing address & register & (initialization OR startup)

[Search within results](#) | [Search Tips](#) | [Try Google Experimental](#)

©2008 Google - [Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)